

## FRAX SB 93047 HONEYCOMB



26000 9390 N

AVAILABLE IN

**FLEMISH BRONZE OUTDOOR** 26000 9390 FBRX

**ANTHRACITE** 26000 9390 N

**PINE GREEN** 26000 9390 PGR



[View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Surface mounted, Wall Surface mounted
<b>INGRESS PROTECTION</b>	IP65
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK06
<b>WEIGHT (KG)</b>	1.3
<b>ADJUSTABILITY</b>	0° to 120° swiveling, 360° rotatable
<b>INFORMATION</b>	4 x LENS SP-14° INCL.LED POWER SUPPLY 700mA-DC INCL.BEAM LENS 47° INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 3 x 1mm <sup>2</sup> 2m

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	CB, ENEC, EPD, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 8W / CRI>90 (R9: 60) / 3000K / 961lm
<b>TM-30 VALUES</b>	Rf: 92 / Rg: 99
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 150000
<b>BEAMANGLE</b>	47°
<b>LED TECHNICS (LIGHT SOURCE)</b>	961lm // 8W // 120lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	490lm // 9W // 53lm/W

### Requirements

FRAX BRACKET  
FRAX PIN  
FRAX STRAP

### Options

FRAX ANTI VANDAL SCREWS

### Accessories

FRAX S KAP

# DELTALIGHT

## FRAX SB 93047 HONEYCOMB

26000 9390 N

For detailed installation instructions, please consult the manual : [26000\\_XX90\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Pins and plates for bollards

---



**26070 0040 FBRX** FRAX PIN FBRX

**26070 0040 N** FRAX PIN N

**26070 0040 PGR** FRAX PIN PGR

#### Fixation components

---



**26070 0060 FBRX** FRAX BRACKET FBRX

**26070 0060 N** FRAX BRACKET N

**26070 0060 PGR** FRAX BRACKET PGR

#### Light altering devices

---



**26070 0010 N** FRAX S KAP N

# DELTALIGHT

## FRAX SB 93047 HONEYCOMB

26000 9390 N

### Other

---



**26070 0030** FRAX ANTI VANDAL SCREWS 5 PCS



**26070 0050 N** FRAX STRAP N



Notes: