



ENTERO RD-S TRIMLESS 93045 GC



28425 9330 GC

ВАРИАНТЫ ЦВЕТА КОРПУСА

ЧЕРНЫЙ 28425 9330 B

ПОЛНОСТЬЮ БЕЛЫЙ 28425 9330 FW

ЗОЛОТО ЦВЕТНОЕ 28425 9330 GC



[Веб страница продукта](#)



Общая информация

ПРЕДНАЗНАЧЕН ДЛЯ УСТАНОВКИ	внутреннее
МОНТАЖ	ПОТОЛОК ВСТРОЕННЫЙ
РАЗМЕР/ФОРМА МОНТАЖНОГО ОТВЕРСТИЯ(ММ)	круглый - Ø KIT
ГЛУБИНА ВСТРАИВАНИЯ	105
ЗАЩИТА ОТ ПЫЛИ И ВЛАГИ	IP20
ВЕС (КГ)	0.235
РЕГУЛИРУЕМОСТЬ	0° to 30° swiveling, 355° rotatable
ИНФОРМАЦИЯ	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 20° & 30° available

Электрические характеристики

ЭЛЕКТРИЧЕСКАЯ КЛАССИФИКАЦИЯ	III
УПРАВЛЕНИЕ	Согласно внешнего блока питания
КЛАСС ПОТРЕБЛЕНИЯ ЭНЕРГИИ	E
СЕРТИФИКАТЫ	CB, ENEC, EPD

Характеристики источника света

LIGHTSOURCE NAME	LED
ТИП ИСТОЧНИКА СВЕТА	LED array 5,8-12,4W / CRI>90 (R9: 52) / 3000K / 787-1467lm
ТМ-30 ЗНАЧЕНИЯ	rf: 90 / Rg: 99
SDCM	SDCM1
ГРУППА РИСКА	RG1
LM80	L90B10 > 50000
ХАРАКТЕРИСТИКИ ИСТОЧНИКА	1467lm // 12,4W // 118lm/W
ХАРАКТЕРИСТИКИ СВЕТИЛЬНИКА	1125lm // 14,3W // 79lm/W

Примечания

Max.500mA when using accessories

Обязательные комплектующие

MOUNTING KIT ENTERO ROUND S

MOUNTING KIT AIR 105

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

ENTERO RD-S TRIMLESS 93045 GC

28425 9330 GC


Аксессуары

- ENTERO S HONEYCOMB
- ENTERO S LINEAR SPREAD LENS
- ENTERO S SPREAD LENS
- ENTERO S SOFTENING LENS
- ENTERO S GLASS SBL

Полная инструкция по монтажу по ссылке: [28425_XXX0_HAND.pdf](#)

ТИП ПОТОЛОЧНОГО МАТЕРИАЛА

Ceiling Type	Mounting Kit
 System ceiling	 MOUNTING KIT ENTERO RD-S O.F.A. Required
 Plasterboard	 MOUNTING KIT ENTERO RD-S O.F.A. Required
 Stucanet	 MOUNTING KIT ENTERO RD-S O.F.A. Required
 Wood	 MOUNTING KIT ENTERO RD-S O.F.A. Required
 Concrete + plaster	 MOUNTING KIT ENTERO RD-S O.F.A. Required
 Lintel + plaster	 MOUNTING KIT ENTERO RD-S O.F.A. Required
 Hollow-core slab + plaster	 MOUNTING KIT ENTERO RD-S O.F.A. Required
 Stretched ceiling	 MOUNTING KIT ENTERO RD-S CSC Required
	 MOUNTING KIT ENTERO RD-S WSC Required
 Ventilation in plasterboard	 MOUNTING KIT SIDE AIR ONLY 1 Required
	 MOUNTING KIT SIDE AIR 105 Required
	 MOUNTING KIT NO AIR 105 Required
 Ventilation in concrete + plaster	 MOUNTING KIT NO AIR 105 Required
	 MOUNTING KIT TOP AIR 105 Required
	 MOUNTING KIT TOP AIR ONLY 1 Required












9

7

 DELTALIGHT®











ENTERO RD-S TRIMLESS 93045 GC

28425 9330 GC

Светодиодные источники питания			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	4(4) 4(4) 4(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	2(2) 2(1) 2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) 6(4) 4(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	3(2) 2(1) 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2) 2(1) 1(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	2 2 2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	3 3 2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	3 3 3	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	3 3 2	☐


ENTERO RD-S TRIMLESS 93045 GC

28425 9330 GC

	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2 0 0	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1 1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->3 2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 2 1	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8	1	☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8	1	☐
	21012 0328 LED POWER SUPPLY 700mA / 15W DIM8	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	2(2)	☐
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68	2(1)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	2(1)	☐


ENTERO RD-S TRIMLESS 93045 GC

28425 9330 GC




21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

☐


21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

☐


21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5


2

☐

Монтажные комплекты




28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.

☐


28400 0070 MOUNTING KIT ENTERO RD-S CSC

☐



28400 0130 MOUNTING KIT ENTERO RD-S WSC

☐


28500 0220 MOUNTING KIT DEEP ENTERO RD-S TRIMLESS

☐

Mounting kits side air + light




29810 0110 MOUNTING KIT SIDE AIR 105

☐

ENTERO RD-S TRIMLESS 93045 GC

28425 9330 GC

Mounting kits top air + light




29810 0130

MOUNTING KIT TOP AIR 105

☐

Mounting kits side air only




29810 0100

MOUNTING KIT SIDE AIR ONLY 1

☐

Mounting kits top air only




29810 0200

MOUNTING KIT TOP AIR ONLY 1

☐

Mounting kits no air



29810 0120

MOUNTING KIT NO AIR 105

☐

 DELTALIGHT®

ENTERO RD-S TRIMLESS 93045 GC
28425 9330 GC

Светопреломляющие устройства



28500 0010

ENTERO S LINEAR SPREAD LENS

☐


28500 0020

ENTERO S SPREAD LENS

☐


28500 0030

ENTERO S SOFTENING LENS

☐

28500 0040

ENTERO S GLASS SBL

☐

28500 0050 B

ENTERO S HONEYCOMB SINGLE USE B

☐

28500 0060 B

ENTERO S HONEYCOMB DOUBLE USE B

☐

ENTERO RD-S TRIMLESS 93045 GC

28425 9330 GC

Сменный отражатель / линза



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

19810 0240 SPY 52 REFLECTOR 30°

☐

Notes: